



28.071 ACRE PARCEL

0.173 acres Right of Way (R/W)

Deed of Record: Permanent Parcel Number (PPN) 03-003-00-020-00, Windsor Road Land, LLC, Document Number (DN) 2021-00015435, Volume 758, Page 2542 of Ashtabula County Records and Deeds (ACRD). 3738 South Ridge Road (East).

Situated in the Township of Ashtabula, County of Ashtabula and State of Ohio and known as being part of Original Lot 2, Old Survey, within said Township and Township 13N, Range 3W in the Connecticut Western Reserve and bounded and described as follows:

Commencing at a 1" iron pin in a monument box found at the centerline intersection of Blake Road (also known as Township Road 406, 60 feet wide) and South Ridge Road (also known as South Ridge Road East, Ohio State Route 84, 60 feet wide).

Thence South 65°11'46" West, along the centerline of said South Ridge Road, 495.37 feet to an angle point therein, referenced by 6" concrete monuments with brass caps bearing "STATE OF OHIO RIGHT OF WAY" found South 24°45'22" East, 29.925 feet and North 24°45'22" West, 29.925 feet therefrom.

Thence South 65°22'12" West, continuing along said centerline, 1099.50 feet to a 1" iron pin in a monument box found at an angle point therein.

Thence South 65°40'53" West, continuing along said centerline, 1590.82 feet to the northwesterly corner of PPN 03-003-00-018-00 as conveyed to Timothy J. Pallutch, recorded in DN 2012-00005370, Volume 517, Page 1314, Tract One of ACRD, being a northeasterly corner of the parcel herein described and <u>The Principal Place of Beginning of this Survey</u>.

Thence South 24°16'14" East, along a westerly line of said Pallutch's land, passing through a 1/2" iron pin in concrete found bent, coned and observed at 30.09 feet (not

28.071 ACRE PARCEL (continued)

on R/W), a total distance of 204.11 feet to a 1/2" iron pin in concrete found at an angle point therein, being a northeasterly corner of the parcel herein described.

Thence South 02°03'15" East, along a westerly line of said Pallutch's land, and also along the westerly line of PPN 03-003-00-019-00 as conveyed to Timothy J. Pallutch, recorded in DN 2012-00005370, Volume 517, Page 1314, Tract Two of ACRD, 250.08 feet to a 1/2" iron pin in concrete found at the southwesterly corner thereof.

Thence North 87°58'42" East, along the southerly line of said Pallutch's land, passing through a 1/2" iron pin in concrete found at 264.75 feet, a total distance of 265.54 feet to a 5/8" iron pin set at the southeasterly corner thereof, on the westerly line of PPN 03-003-00-016-01 as conveyed to Norma I. Rivera, recorded in DN 2015-00004207, Volume 587, Page 272 of ACRD, being a northeasterly corner of the parcel herein described.

Thence South 02°04'32" East, along said westerly line of Rivera's land and also along a westerly line of PPN 03-003-00-012-00 as conveyed to Bonnie J. Pocza and Thomas M. Pocza, recorded in DN 1996-00011163, Volume 89, Page 9545 of ACRD, passing through a 1 1/2" iron pipe found near the top of the northerly bank of the Ashtabula River (also known as Ashtabula Creek) at 1006.23 feet, a 5/8" iron pin set as a corner reference at 1764.87 feet, a total distance of 1834.87 feet to the center of the Ashtabula River, being the southeasterly corner of the parcel herein described.

Thence westerly, downstream, along the center of said River, being the southerly line of said Ashtabula Township, along the northerly line of PPN 42-003-00-038-00 as conveyed to Kathleen Ann Brockway, recorded in DN 2017-00006398, Volume 639, Page 370, PPN 42-003-00-039-00 as conveyed to James W. Munger, recorded in DN 1994-00013760, Volume 76, Page 9551 and PPN 42-003-00-040-00 as conveyed to Christopher B. Brockway, recorded in DN 2017-00006397, Volume 639, Page 367 of ACRD, the following four(4) courses:

- 1.) South 88°11'46" West, 195.00 feet to an angle point therein.
- 2.) South 83°24'28" West, 185.00 feet to an angle point therein.
- 3.) South 62°38'10" West, 90.00 feet to an angle point therein.
- 4.) South 88°48'53" West, 155.84 feet to the southeasterly corner of PPN 03-003-00-021-00 as conveyed to Scott Warren and Amy Warren, recorded in DN 1999-00022124, Volume 116, Page 8712 of ACRD, being the southwesterly corner of the parcel herein described.

28.071 ACRE PARCEL (continued)

Thence North 00°52'08" West, along the easterly line of said Warren's land, passing through a 5/8" iron pin set as a corner reference at 95.00 feet, a 5/8" iron pin set near the top of the northerly bank of the aforesaid Ashtabula River at 846.00 feet and a 5/8" iron pin set at 2198.77 feet, a total distance of 2231.47 feet to the northeasterly corner thereof, on the centerline of the aforesaid South Ridge Road, being the northwesterly corner of the parcel herein described.

Thence North 65°40'53" East, along said centerline, a frontage distance of 245.33 feet to The Principal Place of Beginning of this Survey and containing 28.071 acres of land, of which, 0.173 acres are within the R/W of said South Ridge Road, leaving 27.898 acres exclusive of said R/W, surveyed in January of 2022 by D.B. Kosie and Associates (Robert L. Kosie, Registered Professional Land Surveyor No. 8167). Bearings are to True North using The ODOT VRS and CORS GNSS network (NAD83 - 2011, NAVD88, GRS80, and Geoid18). Be the same, more or less, but subject to all legal highways, conditions, assignments, agreements, easements, restrictions and encumbrances.

The intent of this survey is to more accurately define and resurvey PPN 03-003-00-020-00 as conveyed to Windsor Road Land, LLC, recorded in DN 2021-00015435, Volume 758, Page 2542 of ACRD. Known as 3738 South Ridge Road East.

All 5/8" iron pins set shown herein noted as being 5/8" x 30" iron (steel) rebar pins (#5 rebar) with yellow plastic cap bearing "KOSIE P.S. 8167".



Robert L. Kosie, Sr., Ohio Certified Registered Professional Surveyor 8167

Signed and Sealed on January 3rd, 2-21.